



# XL 18

## GLOSS FLOOR FINISH

Metal Cross Linked with 18% Solids

**Non-Slip Fast Drying  
Premium Floor Finish**

INFUSED WITH  
**INTERSEPT®**  
ANTIMICROBIAL



### Tech Data Sheet

Get exceptional shine with **XL 18 Gloss Floor Finish** when high solids count isn't required. XL 18 provides protection and can be burnished do to it being a cross metal interlinked pure acrylic. Easily maintained and infused with **Intersept®**, this cost effective finish fills the need of general contractor and other budget savvy owners.

#### WHERE TO USE

**XL 18 Gloss Floor Finish** offers a variety of surface applications including VCT, Linoleum, Terrazzo, Rubber, Asbestos Tile, Asphalt Tile, Concrete, Sealed Wood and other resilient floors. Non-resilient floors such as Marble may require testing for adhesion.

#### DIRECTIONS

**PREPARATION:** Seal off areas to be stripped or finished. Floors may be very slippery until dry. Prior to application, floors should be completely stripped of old finish and neutralized. Floors should be completely dry before applying first coat and all subsequent coats. Do not use an air mover or fan to dry finish.

#### INTERSEPT® ANTIMICROBIAL

**Intersept®** is an antimicrobial preservative that protects the cured floor finish against a broad spectrum of bacteria and fungi, including odor - and stain-causing microorganisms.


**Intersept®** is registered with the EPA and meets stringent certification standards set by the three most recognized testing protocols related to indoor environmental quality – the State of Washington Protocol, CRI Green Label and GSA Antimicrobial Certification. Yet, despite its proven ability as a microbial inhibiting preservative, **Intersept®** is low in toxicity and contains no arsenic, heavy metals, phenols or formaldehyde.

#### TECHNICAL SPECIFICATIONS

COLOR: .....	Milk-White	TYPE: .....	Acrylic Polymer
FORM: .....	Liquid	SOLID CONTENT: .....	18%
SCENT: .....	Mild Solvent/Polymer	INITIAL GLOSS: .....	High
pH: .....	8.0 - 9.0	RECOAT DRYING TIME: .....	Minimum 30 Minutes
FLASH POINT: .....	None	COVERAGE: .....	2500 - 3000 sq. ft.
FOAM: .....	None	LEVELING: .....	Excellent
VISCOSITY: .....	Water Thin	SLIP COEFFICIENT: .....	0.57
STORAGE (Unopened): .....	1 Year @ R.T.	REMOVABILITY: .....	Excellent
BIODEGRADABLE: .....	Yes	SCUFF RESISTANCE: .....	Very Good
WEIGHT/GAL: .....	8.5	DETERGENT RESISTANT: .....	Very Good
SHIPPING CLASS: .....	None	HIGH SPEED BURNISH: .....	Yes
PACKAGING: .....	1 Gal., 5 Gal.	DILUTION: .....	Use As Is

#### XL 18 Gloss Floor Finish

**WITHOUT Intersept®**  
Antimicrobial Protection



Aspergillus  
Mold

**WITH Intersept®**  
Antimicrobial Protection

FOR COMMERCIAL AND INDUSTRIAL USE ONLY

©2012 XL North, Fall River, MA 02722 USA

Questions or Comments:  
**888-530-2259**

[www.xlnorth.com](http://www.xlnorth.com)

Another Great  
Product By



Rev. 082012a