



XL

Green Floor Finish

Environmentally Friendly Product

Tech Data Sheet



XL Green Floor Finish is a highly versatile extended-wear, environmentally safe floor sealer/finish, XL Green Floor Finish provides durable protection without creating unwanted build-up. It also allows for easy maintenance as well as exceptional film clarity.

Where To Use: **XL Green Floor Finish** offers a variety of surface applications including VCT, Linoleum, Terrazzo, Rubber, Asbestos Tile, Asphalt Tile, Concrete and other resilient floors. Non-resilient floors such as Marble may require testing for adhesion.

How To Use:

PREPARATION: Seal off areas to be stripped or finished. Floors may be very slippery until dry. Prior to application, floors should be completely stripped of old finish and neutralized. Floors should be completely dry before applying first coat and all subsequent coats. Do not use an air mover or fan to dry finish.

TECHNICAL SPECIFICATIONS

COLOR:	White	TYPE:	Floor Finish
FORM:	Liquid	SOLID CONTENT:	N/A
SCENT:	Acrylic Odor	INITIAL GLOSS:	High
pH:	7.5	RECOAT DRYING TIME:	Minimum 30 Minutes
FLASH POINT:	None	COVERAGE:	2000-2500 sq. ft.
FOAM:	N/A	LEVELING:	Excellent
VISCOSITY:	Water Thin	SLIP COEFFICIENT:	>0.50
STORAGE (Unopened):	1 year minimum	REMOVABILITY:	Excellent
BIODEGRADABLE:	N/A	SCUFF RESISTANCE:	Very Good
WEIGHT/GAL:	N/A	DETERGENT RESISTANT:	Very Good
SHIPPING CLASS:	None	HIGH SPEED BURNISH:	Yes
PACKAGING:	4x1 Gal. Cases	DILUTION:	Use As Is



FOR COMMERCIAL AND INDUSTRIAL USE ONLY

©2014 XL North, Fall River, MA 02722 USA

Questions or Comments:
888-530-2259

www.xlnorth.com



Rev. 020912a